ARMY RESEARCH LABORATORY

ARL

Uniform Tests of File Converters Using Unit Cubes

by Steven J Nichols

ARL-CR-0770   **March 2015**

Under contract

W911NF-10-2-0076

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory
Aberdeen Proving Ground, MD 21005

Uniform Tests of File Converters Using Unit Cubes

Steven J Nichols
Survivability/Lethality Analysis Directorate, ARL

REPORT DOCUMENTATION PAGE		***Form Approved OMB No. 0704-0188***

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.
PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE *(DD-MM-YYYY)*	2. REPORT TYPE	3. DATES COVERED (From - To)
March 2015	Contractor Report	07/2014– 08/2014

4. TITLE AND SUBTITLE	5a. CONTRACT NUMBER
Uniform Tests of File Converters Using Unit Cubes	W911NF-10-2-0076
	5b. GRANT NUMBER
	5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S)	5d. PROJECT NUMBER
Steven J Nichols	
	5e. TASK NUMBER
	5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)	8. PERFORMING ORGANIZATION REPORT NUMBER
US Army Research Laboratory ATTN: RDRL-SLB-S Aberdeen Proving Ground, MD 21005	

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)	10. SPONSOR/MONITOR'S ACRONYM(S)
	11. SPONSOR/MONITOR'S REPORT NUMBER(S)
	ARL-CR-0770

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES

14. ABSTRACT

Ballistic Research Laboratory–Computer-Aided Design (BRL–CAD) is a solid-geometry modeling system used to design and develop geometric systems. It employs a sophisticated ray-tracing software system to evaluate materials, perform calculations, and render images of models of US Army vehicles. Ray-tracing large geometries could require millions of floating-point operations. Also included in BRL–CAD are converters that allow the user to convert from different geometry file types. The goal of this project is to create a uniform test for every file converter. This test is the creation of 1,000-unit cubes, from volume 0 ($0 \times 0 \times 0$) to 1-meter cubed ($1{,}000 \times 1{,}000 \times 1{,}000$), each incrementing by 1 millimeter. This tests the functionality of each converter and allows for comparison. This project was approached by first designing a program that would create 1,000 cubes of sizes incrementing by 1. The program was run in both of the BRL–CAD geometry editors before the files were changed to fit into the parameters of the other formats, allowing for the conversion of all different file types.

15. SUBJECT TERMS
converter, BRL–CAD, file, cube

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
					Geoffrey Sauerborn
A. Report	b. ABSTRACT	c. THIS PAGE	UU	14	19b. TELEPHONE NUMBER *(Include area code)*
Unclassified	Unclassified	Unclassified			410-278-6178

Contents

List of Figures

Acknowledgments

Student Biography

Steven J Nichols is a senior at the Science and Mathematics Academy at the Aberdeen High School in Maryland. He hopes to attend college and earn a computer-engineering degree. This is his first research experience.

1.   Introduction/Background

Ballistics Research Laboratory–Computer-Aided Design (BRL–CAD) is a solid-modeling software system that was developed in the early 1980s as a way to model US Army vehicles. It uses an advanced ray-tracer to render models. Previously, it only rendered with Constructive Solid Geometry, in which Boolean operations are applied to simple primitives such as being added and subtracted from each other as well as using their intersection to create a nearly infinite number of shapes. Another feature of BRL–CAD is its set of geometry converters. Currently, it has the largest converter library in open-source software and is constantly expanding. Some converters have not been tested in decades, if at all.

2.   Experiment/Calculations

Before the actual experiment, about 2 weeks were spent digitizing historical tapes and learning the C language. During this time, tapes from as early as the 1970s were recorded and saved on a computer for their historical value. These tapes included tech demos of new features being added to BRL–CAD, promotional videos for BRL–CAD (Fig. 1 shows its historic logo), and even details of the historic Cray supercomputer.

Fig. 1   Old historic BRL–CAD logo (left) and current logo (right)

My main project was to support testing all BRL–CAD file converters using a set of unit cubes. This was a set of 1,000 cubes ranging in dimensions from 1 mm × 1 mm × 1 mm to 1,000 mm × 1,000 mm × 1,000 mm. When rendered, these 1,000 cubes would appear as a single cube (as shown in Fig. 2).


Fig. 2 Converter test cube set

The converters were split into 3 groups: those with both importers and exporters, those with importers only, and those with exporters only. Those with both importers and exporters were the easiest as the only thing that was needed was to convert the file using the built-in converter in command line. The file was converted to the new format using command line and then converted back using a different built-in converter. One notable example was the STereoLithography (STL) format converter. This converts the entire geometry into a triangular mesh (as shown in Fig. 3) and otherwise remains the same in terms of volume and area. However, most of the converters keep the model in cubes (as displayed in Fig. 4).


Fig. 3   Single cube in STL

Fig. 4   Single cube in *.g*

For the importers only, the issue was "tricking" BRL–CAD into accepting the file as the file type that it required to convert back into a *.g* file. One example would be the FASTGEN format. This file type is able to raytrace completely flat (Plate Mode) geometry. Although it was not a problem faced during the project, it is something that needs to be considered in the future.

For the exporters only, the main challenge was to find a way to convert the file back into a *.g* file without messing it up on the user end. This was less difficult than the importers because it was much more uniform in the way that the file needed to be. There were no file types that were in continual use that were exporters only. The only example was the ACAD format that was used by Lockheed Martin.

3. Results and Discussion

From the converters tested, there were none that seemed to be incorrect from the tests. The tests involved 2 steps. The first was finding the volume of the bounding box of the entire shape. The bounding box is the smallest rectangular prism that can contain the entirety of the geometry. Because of the nature of the test (being made entirely out of cubes) the bounding box would also be the volume of the largest cube. A successful test would result in a volume of 1 m^3 or 1,000,000,000 mm^3. The second part would be to test each face of the cube using the *rtarea* command, which finds the exposed surface area of all of the exposed objects. Any deviation of

size in the bounding box would indicate that the size of the cubes was not preserved and instead was warped in some way, or the cubes' dimensions were not that of the original.

4. Summary and Conclusions

Converters in BRL–CAD allow for easy importation and exportation of files from various types. This is useful because of the necessity to bring in files to BRL–CAD as well as the demand for it as a fast and easy tool. This allows BRL–CAD to act as a hub for conversion and, in turn, increases the number of users of BRL–CAD. The converters all work well, considering the age of some of them and the fact that changes in their target formats are not under the control of BRL–CAD. However, this might be countered by the fact that BRL–CAD has also been maintained and has one of the longest histories of traceable software changes of any open-source project.

List of Symbols, Abbreviations, and Acronyms

ACAD   AutoComputer-Aided Design

BRL–CAD   Ballistic Research Laboratory–Computer-Aided Design

FASTGEN   Fast Shotline Generator

GDiff   Geometry Differences

GUI   graphical user interface

STL   STereoLithography